

# Geo-Instruments: WiSe Tiltmeter System

Geo-Instruments Tilt-Sensors are an easy way to detect differential movement and rotation in structures.

Typical applications include:

- Effects of deep excavations and diaphragm wall construction on adjacent existing structures
- Ensure stability of structures affected by tunneling and mining activities
- Monitor deformation within tunnels including convergence

Benefits to this system are:

- Robust, accurate, simple and reliable
- Very cost effective as compared to other settlement profiling systems
- Good long term stability
- Installable on discrete points e.g. walls, ceilings or even non-vertical surfaces

This system has also been integrated with our WiSe data logging system. For more information on WiSe, please see the WiSe System Datasheet.



Range	+/- 45 Arc Minutes
Accuracy	+/- 0.1mm/m
Resolution	0.02% Full Scale
Repeatability	+/- 0.05% Full Scale
Excitation Voltage	2.5v AC
Current Consumption	<1µA
Output Signal	Ratiometric AC
Operating Temperature	-20 to +50° C
Zero Adjustment Range	+/- 5° Fine +/-25° Course
Ingress Protection	IP66

At Right: Wise paired with tiltmeter unit shown on angle bracket.

Note: Tiltmeter can also be mounted vertically on 1.5 inch beam sensor stock in application where right angle bracket is inappropriate.

Phone: 800-477-2506  
 Fax: 401-633-6021  
 E-mail: sales@geo-instruments.com

24 Celestial Drive  
 Suite B  
 Narragansett, R.I. 02882

Helping you get the  
 data you need.

