



ClimaVUE™50

The ClimaVUE 50 from Campbell Scientific is a complete weather station. Compact, low power, and simple to install, it has no moving parts and requires minimal maintenance.

Measurements

- Air temperature
- Barometric pressure
- Vapor Pressure
- Relative humidity
- Precipitation
- Wind direction
- Wind speed
- Solar radiation
- Lightning strike
- Lightning average distance
- Tilt (to ensure accuracy of rain gauge)

Air Temperature

Measurement Range: -50° to +60°C
Resolution: 0.1°C
Accuracy: ±0.6°C

Barometric Pressure

Operating Temperature: -40° to +60°C
Measurement Range: 500 to 1100 hPa
Resolution: 0.1 hPa
Accuracy: ±1 mb (-10° to +50°C) or
±5 mb (-40° to +60°C)

Vapor Pressure

Measurement Range: 0 to 47 kPa
Resolution: 0.01 kPa
Accuracy or Repeatability: ±0.2 kPa typical
below 40°C.

Relative Humidity

Measurement Range: 0 to 100%
Resolution: 0.1
Accuracy: ±3% RH typical

Precipitation

Measurement: 0 to 400 mm/h (15.75 in./h)
Resolution: 0.017 mm
Accuracy: ±5% of measurement
(from 0 to 50 mm/h or 0 to 1.97 in./h)

Wind Speed

Wind Speed Maximum: 10 s gust
Measurement Range: 0 to 30 m/s (0 to 67 mph)
Resolution: 0.01 m/s (0.02 mph)
Accuracy or Repeatability: 0.3 m/s or 3% (0.67 mph or 3%), whichever is greater

Wind Direction

Measurement Range: 0° to 359°
Resolution: 1°
Accuracy: ±5°

Solar Radiation

Measurement Range: 0 to 1750 W m-2
Resolution: 1 W m-2
Accuracy: ±5% of measurement (typical)
Spectral Range: 300 to 1150 nm

Lightning Strike Count

Measurement Range: 0 to 65,535 strikes
Resolution: 1 strike
Accuracy: > 25% detection at < 10 km typical
(variable with distance)

Lightning Average Distance

Measurement Range: 0 to 40 km (0 to 24.9 mi)
Resolution: 3 km (1.86 mi)
Accuracy: Variable

Tilt

Measurement Range: -90° to +90°
Resolution: 0.1°
Accuracy: ±1°

Power

Min Supply Voltage: 3.6 Vdc continuous
Max Supply Voltage: 15.0 Vdc continuous
Typical Current Drain @ 12 Vdc: < 1 mA
(average)

Power Consumption

Quiescent: 0.3 mA
Maximum Peak Current: 33 mA
Average (R7! Command every 10s): 1.0 mA
Average (R7! Command every 60s): 0.4 mA

General

Output: SDI-12
Compatibility: Any modern CSI data logger
Operating Temperature Range: -50° to +60°C
(barometer and RH: -40° to +60°C)
Typical Measurement Duration: 110 ms
Maximum Measurement Duration: 3,000 ms
Maximum Polling Frequencies: 10 s

Size & Weight

Diameter: 10 cm (4 in.) with rain gage funnel
Height: 34 cm (13.4 in.) with rain gage funnel
Weight: 839.15 g (1.85 lb)

ClimaVUE 50™ is a trademark of Campbell Scientific. Image courtesy of Campbell Scientific.